

PL AQUA PRO

TECHNICAL FEATURES

	PL AQUA PRO	PL AQUA PRO BIG
Raw material:	PES	PES
Core:	PP	PP
Outer cage:	PP	PP
End caps:	DOE-PP	DOE-PP
O-Ring / Gasket:	NBR	NBR
Length:	9"3/4-20	9"3/4-20
Inner diameter:	28 mm	28 mm
Outer diameter:	70 mm	116 mm
Micron/rating:	3/20/50	20/50
Efficiency:	95%	95%
Pressure:		
Max working pressure:	6 bar	6 bar
Max differential pressure:	0,8 bar	0,8 bar
Temperatura/ emperature:		
Max working temperature:	80°C	80°C
pH min - max	3-9	3-9

Portata max in lt/h di acqua a 20°C e differenza di pressione 0,15 bar/Max water flow rate at 20°C and differential pressure 0,15 bar



CARTUCCE POLIESTERE PIEGHETTATO serie PL AQUA PRO
PLEATED POLYESTER CARTRIDGES series PL AQUA PRO

CODICE CODE	MICRON	ALTEZZA LENGHT	QUANTITÀ QUANTITY scatola-	Kg scatola-	VOLUME conf-
A4080230	3	9"3/4	15	4,70	0,030
A4080240	3	20"	15	9,07	0,035
A4080140	20	9"3/4	15	4,70	0,030
A4080160	20	20"	15	9,07	0,035
A4080150	50	9"3/4	15	4,70	0,030
A4080170	50	20"	15	9,07	0,035



CARTUCCE CARTA PIEGHETTATA serie PL AQUA PRO BIG
PLEATED CELLULOSE CARTRIDGES series PL AQUA PRO BIG

CODICE CODE	MICRON	ALTEZZA LENGHT	QUANTITÀ QUANTITY scatola-	Kg scatola-	VOLUME conf-
A4080180	20	9"3/4	6	4,32	0,030
A4080200	20	20"	6	8,69	0,035
A4080190	50	9"3/4	6	4,32	0,030
A4080210	50	20"	6	8,69	0,035

Importőr, Kis- és Nagykereskedés, Szerviz





VL

SZIVATTYÚJAVÍTÓ
IP. KER. SZOLG.BT.

H-2225 Üllő, Bimbó u. 4. Tel/fax.:06/29-320-150, 29-321-160
www.vlbt.hu info@vlbt.hu