

JA 106N-126-146

WHAT IS IT

Self-priming centrifugal pump for water supplies (even if mixed with gas) in small household systems, connected to autoclave tanks, for transferring liquids and emptying tanks; also used for gardening.

MAIN USES



water supply and pressurization for irrigation of gardens and small cultivations



Water supply and pressurization for domestic and residential installations

SPECIFICATIONS

Pump Body	Cast iron
Motor bracket	Cast iron
Impeller	Noryl or Brass
Mechanical seal	Ceramic-Graphite
Motor shaft	Stainless steel AISI 416
Liquid temperature	0-50 °C
Operating pressure	Max 7 bar
Insulation class	F
Suction-delivery pump fitting	G 1" threaded F



APPLICATIONS

	1 STOREY	2 STOREYS	3 STOREYS
	-	JA 106N	JA 146
	JA 106N	JA 106N	JA 146
	JA 106N	JA 146	-
	JA 146	JA 146	-

PLUS & PERFORMANCE



New self-priming system



Increased range of models



Better performance

JA 106N

m^3/h	1,2	2,4	4,2
l/min	20	40	70
$H(m)$	38,9	30,1	20

JA 126

m^3/h	1,2	2,4	4,2
l/min	20	40	70
$H(m)$	42,6	33,5	23

JA 146

m^3/h	1,2	2,4	4,2
l/min	20	40	70
$H(m)$	55,7	39,5	28,1